

Large-Scale Shared AV Simulations with Geofences, Stop Aggregation, & Parking Restrictions



Kara Kockelman

University of Texas at Austin

with UT's Murthy Gurumurthy & Haonan Yan + ANL's Josh Auld





Case Study #1: 4 Chicago Geofences

Different
 population-to jobs ratios
 across
 geofences.

 Pop/jobs < 2 for City, Suburban, & Exurban Core.


≈ 2.15 for entire region







%eVMT by Scenario



Note: Base Case = Ridehailing with conventional vehicles



Fencing Results


Assuming fewer cars desired per household, **just 1 SAV per 100 residents**, & \$0.50/mile SAV fares:

- Unfenced/full-region service has 11 min avg. response time
 + 35% (!) eVMT, with SAV mode split of ~6%.
- Geofencing <u>lowers</u> response times & eVMT, with greatest reductions within (sub)urban core.
- Avg. response times vary linearly with proximity to CBD.
- Dynamic ride-sharing (with strangers) lowers %eVMT by another 2-10%.
- Net VMT savings up to 5% (no DRS) & 9% (DRS) thanks to smaller fences.
- City-wide fence implies < 1 SAV/100 Residents fleet size for comparable trips served/SAV → non-linear fleet requirement.



Case Study #2: Pickup & Dropoff Stops (PUDOs) in Bloomington, Illinois

- Bloomington, Illinois
 - Just 74 sq. miles
 - 120,000 residents
 - 4,000 links + 2,500 nodes
 - About 2,800 unique locations
- POLARIS moves travelers between all O's & D's.
- PUDO stop clustering using pre-defined stop spacing, d_s
 - → Equi-distant stops



 $d_s = 0.25 \text{ mi} = 400 \text{ m}$

Scenarios


- Trip intensities: 100%, 500%, & 2500% to approximate a major city.
 - 25x provides about 15M trips/day or 8,500 person-trips per hour per sq. mile.
 - Travel times rise too, so mode splits need to be unchanged for ideal comparison.
- Fleet sizes scaled up, so each SAV serves 70 persontrips per day, on average.
- SAVs considered for match if < 10 min away.
- All travelers assumed willing to use DRS (ridesharing).
- DRS matching ends if > 5 min or 5% delay (vs. direct travel time).
- PUDO stop spacings of d_s = 0, 0.25, & 0.5 mile tested.

Results

- 7-8% of trip-makers choose SAVs.
 - Between 48k (1x) to 1.2M (25x)
 trips served each day.
- With<u>out</u> DRS & PUDO Stops:
 - Average SAV serves 65 trips/day.
 - Travels approx. 430 mi/day (!)
 - % eVMT about 34% (!)
 - 2-5% lower eVMT with 5x & 25x trip density.




- 5 more trips/SAV/day, 19% eVMT, & 2% less total SAV VMT.
- But longer response & travel times.





DRS + Stops


- <u>Total VMT</u> falls by 1 to 3%.
- SAV VMT savings of 10-20% possible, with more savings from 5x & 25x trip density than from stops.





Temporal Distribution of Avg Vehicle Occupancy (#passengers)

- PUDOs increase AVO
 & lower total VMT by
 aggregating low density trips at off peaks.
- Aggregating trips at any time of day or day of week lowers user costs, empty VMT, & overall VMT.




Stop Aggregation Takeaways

- DRS does help lower congestion but really depends on travelers' willingness to be delayed.
- Higher trip density settings can lower total VMT.
- High parking prices can shift mode shares to SAVs & transit → boosting savings!
- Stops help marginally increase AVO & lower VMT assuming no disutility from walking.
- Dedicated infrastructure may be needed to accommodate SAVs at stops.
- Link characteristics (larger capacity & walkability) may be important for stop placement.



Case Study #3: SAV Parking Restrictions in the Twin Cities


- 9.5M persontrips/day across 7 MPO counties.
- MATSim used across 325k links & 131 nodes, ignoring external + trucks trips.





Restricting Curb Idling

- 134 parking lots with 500-vehicle capacity along links with > 400 trip stops (O's & D's) per curb per day.
- SAVs dropping off pax at those curbs, seek closest parking lot. If no spaces are available at closest 2 lots, SAVs will idle at the curb.



SAV Parking Lot Sites across 7 Counties



SAV Parking Lot Sites in Twin Cities



MSP Parking Results

- Curb parking restrictions across 7 counties generated
 8% more SAV VMT & 7% more eVMT on average.
- SAV work durations (run times per day) rose 15%.
- # DRS trips fell 5%.
- Curb parking restrictions lowered DRS trips by 0.5%, while increasing wait times by 11% & 19% in the 7-county & Twin Cities scenarios, respectively.







More Twin Cities Results

- Using 1:5 SAV-to-traveler fleet, eVMT averaged 7.2% to 14% of total VMT, with each SAV working 4.0 to 8.9 hours per day.
- Smaller fleets of 1:15 has higher eVMT (17 to 23%) & run times ranging from 7.2 to 18 hr/day.
- When DRS is enabled, average response times fall 10%.
- Relative to the 7-county service area, Twin Cities simulations averaged 25% more DRS trips & 19% shorter wait times.
- eVMT occurred mostly in neighborhoods with lower trip-end density
 & dispersed directions.
- Most SAV VMT & eVMT occur on freeways & highways across MSP region.
- As with Chicago, MSP response times are similar across the region!



Thank you!

Questions & Suggestions?



30+ CAV papers & reports at www.caee.utexas.edu prof/kockelman